



US006344752B1

(12) **United States Patent**
Hagihara et al.

(10) **Patent No.:** **US 6,344,752 B1**
(45) **Date of Patent:** **Feb. 5, 2002**

(54) **CONTACTOR AND PRODUCTION METHOD FOR CONTRACTOR**

(75) Inventors: **Junichi Hagihara, Sendai; Shinji Iino, Kitakoma-gun, both of (JP)**

(73) Assignee: **Tokyo Electron Limited, Tokyo (JP)**

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/509,546**

(22) PCT Filed: **Jul. 29, 1999**

(86) PCT No.: **PCT/JP99/04090**

§ 371 Date: **Apr. 12, 2000**

§ 102(e) Date: **Apr. 12, 2000**

(87) PCT Pub. No.: **WO00/10016**

PCT Pub. Date: **Feb. 24, 2000**

(30) **Foreign Application Priority Data**

Aug. 12, 1998 (JP) 10-241036
Aug. 12, 1998 (JP) 10-241037

(51) Int. Cl.⁷ **G01R 31/02**

(52) U.S. Cl. **324/754; 324/762**

(58) Field of Search **324/754, 757, 324/761, 762, 73.1, 758, 765, 72.5; 439/482**

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,177,438 A * 1/1993 Littlebury et al. 324/754
5,476,211 A 12/1995 Khandros
5,625,298 A 4/1997 Hirano et al.

5,811,982 A * 9/1998 Beaman et al. 324/762
5,828,226 A 10/1998 Higgins et al.
5,832,601 A 11/1998 Eldridge et al.
6,218,203 B1 * 4/2001 Khoury et al. 438/15

FOREIGN PATENT DOCUMENTS

JP	7-283280	10/1995
JP	8-50146	2/1996
JP	9-148389	6/1997
JP	11-133062	5/1999
JP	11-145172	5/1999

* cited by examiner

Primary Examiner—Ernest Karlson

Assistant Examiner—Minh N. Tang

(74) *Attorney, Agent, or Firm*—Oblon, Spivak, McClelland, Maier & Neustadt, P.C.

(57) **ABSTRACT**

A conventional probe card is very complex in a support structure of probe terminals and it has been difficult to change an array of the probe terminals correspondingly to various arrays of electrode pads of an object to be checked. A contactor (1) of the present invention simultaneously sets its probe terminals in contact with a plurality of electrode pads of an object to be checked and electrical checking of the object is made once or a plurality of times. It has a plurality of first electrodes (3) arranged on a first substrate (silicon substrate) (2) and probe terminals (4) respectively provided on these electrodes (3). The probe terminal (4) has a conductive support (7) provided on the first electrode, elastic support plate (8) whose one end is fixed to the upper end of the conductive support column (7), and probe terminal (bump) 9 fixed to the free end portion of the elastic support plate (8).

21 Claims, 8 Drawing Sheets

